

STREET

In R-60, R-90, R-150, R-200 standard method zones WHEN ESTABLISHED BUILDING LINE IS REQUIRED

All new construction of houses or main buildings

All Proposed additions:

270RY

Established Bldg, Line Calculation

for addition to Lot 15:

CANTILEVERED

Corner lots have EBL on both streets. Exceptions: 2nd story additions & side additions not extending beyond the existing front of the building,

## INCLUDE IN CALCULATION:

Between intersecting streets and within the same block All bldgs, within 500' of side property lines of subject property,

Bldgs, existing at time permit application is filed

Any cantilevered second story.

Bay window & vestibule more than  $10^{\circ}$  in width or projecting more than 5Upen steps, stoop, terraces or covered porches projecting more than  $9~\mathrm{ft}$ 

## EXCLUDE FROM CALCULATION!

Subject property.

Jorner lots

Pipestem, tlag-shaped or lots not meeting min, width @ min, front setback Houses with front setback variances

Bldgs, with nonconforming front yard setbacks

Bay window & vestibule |O' or less in width and projecting not more than  $\mathcal{S}'$ Upen steps, stoops, terraces or covered porches projecting  $9^{\circ}$  or less.

Revised OI/O4 Scale: |11 = 60 | by 5 lots = 30,51' is EBL not included, corner lot 152' 7" or 152,56' divided 32' 2" or 32,16' not included, subject property

12/4

35' 711 or 35,58' 27'5" or 27,41"

=

5| 711 or 5|,58

not included, pipestem lot

25' | 0" or 25,85'

ESTABLISHED BUILDING LINE